

# TAPE COMPARISON CHART

	Color	Roll Size	Thickness	Backing	Adhesive	Tensile Strength	Peel Adhesion - Stainless Steel	Accelerated Weather Test
<b>True Tape</b> Sheathing Tape	Clear w/ Black letters	3 inch x 330 feet	1.6 mil	Polypropylene	Hot Melt Rubber	37 LBS/ INCH	50 OZ/INCH	-35 to 220 Degrees Fahrenheit
<b>Weather Tape</b> Housewrap Tape	White w/ Blue letters	3 inch x 330 feet	1.6 mil	Polypropylene	Hot Melt Rubber	37LBS/ INCH	50 OZ/INCH	-35 to 220 Degrees Fahrenheit
<b>Cantech</b> UV Treated Polypropyl- ene Tape	Clear, Re d and White	3 inch x 165 feet	3.0 mil	Polypropylene	Acrylic Solvent	30 LBS/ INCH	40 OZ/INCH	14 to 122 Degrees Fahrenheit
<b>Tyvek</b> DuPont Contractor Tape	White	2 inch x 165 feet	3.0 mil	Oriented Polypropylene	Acrylic	27 LBS/ INCH	90 + OZ/INCH	-40 to 220 Degrees Fahrenheit
<b>Styrofoam</b> All-Purpose Tape	Blue	3 inch x 165 feet	3.0 mil	Polypropylene	Acrylic	20,000 LBS/ INCH	75 OZ/INCH	-40 to 150 Degrees Fahrenheit
<b>3M Product # 313</b>	Clear & Tan	2 inch x 328 feet	2.55 mil	Polypropylene	Acrylic	35 LBS/ INCH	24 OZ/INCH	-30 to 130 Degrees Fahrenheit
<b>3 M Product #371</b>	Clear, Tan, Blue, Green, Orange, Red, White, Yellow	2 inch x 328 feet	1.9 mil	Polypropylene	Synthetic Rubber	22 LBS/ INCH	40 OZ/INCH	-30 to 130 Degrees Fahrenheit
<b>Venture Tape</b> Red Sheathing Tape	Red	3 inch x 216 feet	3.0 mil	Polypropylene	Acrylic	20 LBS/ INCH	65 OZ/INCH	10 to Elevated temps Degrees Fahrenheit
<b>Intertape Polymer Group</b> Sheathing Tape	Red	2 inch x 150 feet	3.4 mil	Polypropylene	Solvent Cast	32 LBS/ INCH	64.5 OZ/INCH	-40 to Elevated temps Degrees Fahrenheit

All data shown is from the manufacturers literature. Copies are available upon faxed request 419-636-9292. If there is information missing on the tech data sheets, it was found on the manufacturers website.