

True Tape

Sheathing Tape

1. PRODUCT NAME

True Tape
Sheathing Tape

2. MANUFACTURER

Chardan Specialties
705 S. Union St.
Bryan, OH 43506
Phone: (419) 636-6900
Fax: (419) 636-9292

3. PRODUCT DESCRIPTION

Basic Use: **True Tape** is ideal in the construction industry for seaming foam insulation and aluminum faced products, replacing air barrier type products, seaming polyethylene sheeting, waterproofing around windows and doors, splicing, sealing and patching and applications where long-term aging characteristics are required.

Limitations: **True Tape** should not be applied at temperatures below 20 degrees Fahrenheit.

Composition and Materials: **True Tape** is continuous lengths of polypropylene tape. Three millimeters thick, and clear with blue lettering.

Packaging: **True Tape** is available in 330 foot lengths by 3 inch wide rolls. Twenty-four rolls per case and they are shipped via UPS.

4. TECHNICAL DATA

True Tape is flexible even in lower temperatures. Easily contours to almost any surface. Adhesive is a heavy

coatweight of stable pressure sensitive material for use on plastics, metal, glass and many other materials. The adhesive is excellent indoors and out, unaffected by U.V. rays (there may be slight color fading after prolonged exposure). **True Tape** should not be left exposed in excess of 90 days. **True Tape** provides a strong, yet flexible barrier, is moisture proof, inert and non-conductive. **True Tape** protects against corrosion, fungi and bacteria in below ground installations.

5. INSTALLATION

Preparatory Work: Surface must be clean and free of any foreign materials.

Methods: Either cut the desired length of **True Tape** or dispense directly from reel with tape dispenser.

Precautions: Do not puncture **True Tape** during application.

6. AVAILABILITY AND COST

True Tape is available through

TECH DATA

7—24-07

stocking distributors and lumber dealers or by calling Chardan Specialties for your nearest source.

7. WARRANTY

True Tape is warranted to be free of defects in manufacture. The manufacturer cannot and does not guarantee results from the use of the information provided and disclaims all liability from any loss or damage. No warranty, express or implied, is given as to the merchantability, fitness for a particular purpose, or otherwise with respect to the product.

8. MAINTENANCE

No maintenance is required.

9. TECHNICAL SERVICES

Chardan Specialties representatives are available to provide technical assistance.

10. FILING SYSTEMS

Additional manufacturer's information available upon request.

